



LIONSHEAD

Tire and Wheel Specifications

Radial Specifications

Size	Ply	Maximum Load (lb)	Pressure
ST145R12 LRD	8	1220	65PSI
ST145R12 LRE	10	1520	80PSI
ST175/80R13 LRC	6	1360	50PSI
ST185/80R13 LRD	8	1710	65PSI
ST205/75R14 LRC	6	1760	50PSI
ST205/75R14 LRD	8	2040	65PSI
ST205/75R15 LRC	6	1820	50PSI
ST205/75R15 LRD	8	2150	65PSI
ST225/75R15 LRC	6	2150	50PSI
ST225/75R15 LRD	8	2540	65PSI
ST225/75R15 LRE	10	2830	80PSI
ST235/75R15 LRC	6	2340	50PSI
ST235/75R15 LRD	8	2910	65PSI
ST235/80R16 LRE	10	3520	80PSI
ST235/85R16 LRE	10	3640	80PSI
ST235/85R16 LRF	12	3690	95PSI
ST235/80R16 LRG	14	4080	110PSI
ST235/85R16 LRG	14	4400	110PSI
LT225/75R16 LRE	10	2680 single/2470 dual	80PSI
LT235/85R16 LRE	10	3420 single/2778 dual	80PSI
LT235/85R16 LRG	14	3750	110PSI
LT315/70R17 LRD	8	3195 single/2910 dual	50PSI
215/75R17.5 LRH	16	4805 single/4546 dual	123PSI
235/75R17.5 LRH	16	6005 single/5675 dual	128PSI
245/70R19.5 LRG	14	4540 single/4410 dual	110PSI

Aluminum Wheel Specifications

Size	Bolt Pattern	Maximum Load (lb)
12x4	5-4.5	1520
13x5	5-4.5	1710
14x5	5-4.5	2040
15x5	5-4.5	1820
15x6	5-4.5	2200
15x6	6-5.5	2830
16x6	6-5.5	3300
16x6	8-6.5	4080
16x6	8-6.5 HD	4400
17.5x6.75	8-6.5 (9/16")	4850
17.5x6.75	8-6.5 (5/8")	6050

Steel Wheel Specifications

Size	Bolt Pattern	Maximum Load (lb)
8x7	5-4.5	1075
10x6	5-4.5	1535
12x4	5-4.5	1520
13x4.5	5-4.5	1710
14x5	5-4.5	2200
15x5	5-4.5	2150
15x6	5-4.5	2200
15x6	6-5.5	2830
16x6	6-5.5	3300
16x6	8-6.5	4080
16x6	8-6.5 HD	4400
17.5x6.75	8-6.5 (5/8")	6005